

NODX

Xpand Basic SATA Enclosure

P/N: E01010

www.nodx.life

ATTENTION

Read all the instructions before using the product.

- The product is designed for use with IT equipment only.
- Avoid extreme temperature (>40 °C).
- Naked flame sources, such as candles, must not be placed on the product.
- Don't expose to liquid.
- If you want to clean the product, only use a dry cloth or brush.
- This product is not intended to be repaired by service personnel in case of failure or component defect (the product can be disposed of).
- Do not disconnect the hard drive enclosure or the hard drive during data transferring in case of files missing or the disk damage.
- Please backup hard disk data in advance before hard disk partition or formatting.
- Works with USB 5±0.2V power supply and exceeding the standard voltage range may cause damage to the product or cause potential safety problems.
- It will enter Sleep Mode without any operation in 3 minutes.
- Activate the "Safe Remove" from the computer setting before removing disks.

SPECIFICATION

- Output: SATA 7+15 Pin
- Supports UASP transport protocol
- Supports SATA II, backwards compatible with SATA II
- Supports standard notebook 2.5" SATA thickness less than 9.5mm
- Transfer Rates Up to 5Gbps when connected to a USB 3.0 port backward compatible with USB 2.0 or 1.1

WARRANTY INFORMATION

A 12-month warranty covers all NODX products purchased from the NODX official store or authorized sellers. Please do not hesitate to reach out to us if you experience any issues with our products.

CONTACT

- 🌐 www.nodx.life
- ✉ support@nodx.life